

**10707**

# **Deep Learning**

Russ Salakhutdinov

Machine Learning Department

[rsalakhu@cs.cmu.edu](mailto:rsalakhu@cs.cmu.edu)

Neural Networks I


# Neural Networks Online Course

- **Disclaimer:** Much of the material and slides for this lecture were borrowed from Hugo Larochelle's class on Neural Networks:  
<https://sites.google.com/site/deeplearningsummerschool2016/>

- Hugo's class covers many other topics: convolutional networks, neural language model, Boltzmann machines, autoencoders, sparse coding, etc.


- We will use his material for some of the other lectures.

[http://info.usherbrooke.ca/hlarochelle/neural\\_networks](http://info.usherbrooke.ca/hlarochelle/neural_networks)




# Feedforward Neural Networks

- ▶ How neural networks predict  $f(x)$  given an input  $x$ :
  - Forward propagation
  - Types of units
  - Capacity of neural networks
- ▶ How to train neural nets:
  - Loss function
  - Backpropagation with gradient descent
- ▶ More recent techniques:
  - Dropout
  - Batch normalization
  - Unsupervised Pre-training



# Feedforward Neural Networks

- ▶ How neural networks predict  $f(x)$  given an input  $x$ :
  - Forward propagation
  - Types of units
  - Capacity of neural networks
- ▶ How to train neural nets:
  - Loss function
  - Backpropagation with gradient descent
- ▶ More recent techniques:
  - Dropout
  - Batch normalization
  - Unsupervised Pre-training



# Artificial Neuron

- Neuron pre-activation (or input activation):

$$a(\mathbf{x}) = b + \sum_i w_i x_i = b + \mathbf{w}^\top \mathbf{x}$$

- Neuron output activation:


$$h(\mathbf{x}) = g(a(\mathbf{x})) = g(b + \sum_i w_i x_i)$$

where

$\mathbf{w}$  are the weights (parameters)

$b$  is the bias term

$g(\cdot)$  is called the activation function




# Artificial Neuron

- Output activation of the neuron:

$$h(\mathbf{x}) = g(a(\mathbf{x})) = g(b + \sum_i w_i x_i)$$

Range is  
determined  
by  $g(\cdot)$



(from Pascal Vincent's slides)


Bias only changes  
the position of the  
riff

# Activation Function

- Linear activation function:

- No nonlinear transformation
- No input squashing

$$g(a) = a$$




# Activation Function

- Sigmoid activation function:

- Squashes the neuron's output between 0 and 1
- Always positive
- Bounded
- Strictly Increasing

$$g(a) = \text{sigm}(a) = \frac{1}{1+\exp(-a)}$$




# Activation Function

- Hyperbolic tangent (“tanh”) activation function:

- Squashes the neuron’s activation between -1 and 1
- Can be positive or negative
- Bounded
- Strictly increasing  
(wrong plot)

$$\begin{aligned}g(a) &= \tanh(a) = \\&= \frac{\exp(a) - \exp(-a)}{\exp(a) + \exp(-a)} = \frac{\exp(2a) - 1}{\exp(2a) + 1}\end{aligned}$$




# Activation Function

- Rectified linear (ReLU) activation function:

- Bounded below by 0 (always non-negative)
- Tends to produce units with sparse activities
- Not upper bounded
- Strictly increasing


$$g(a) = \text{relin}(a) = \max(0, a)$$



# Decision Boundary of a Neuron

- Binary classification:

- With sigmoid, one can interpret neuron as estimating  $p(y = 1|\mathbf{x})$
- Interpret as a **logistic classifier**




Same idea can be applied  
to a tanh activation

(from Pascal Vincent's slides)


# Capacity of a Single Neuron

- Can solve linearly separable problems.



# Capacity of a Single Neuron

- Can not solve non-linearly separable problems.



- Need to transform the input into a better representation.
- Remember **basis functions!**

# Single Hidden Layer Neural Net

- Hidden layer pre-activation:

$$\mathbf{a}(\mathbf{x}) = \mathbf{b}^{(1)} + \mathbf{W}^{(1)}\mathbf{x}$$

$$(a(\mathbf{x})_i = b_i^{(1)} + \sum_j W_{i,j}^{(1)}x_j)$$


- Hidden layer activation:

$$\mathbf{h}(\mathbf{x}) = g(\mathbf{a}(\mathbf{x}))$$

- Output layer activation:

$$f(\mathbf{x}) = o\left(b^{(2)} + \mathbf{w}^{(2)^\top} \mathbf{h}^{(1)} \mathbf{x}\right)$$

Output activation  
function



# Softmax Activation Function

- ▶ Remember **multi-way classification**:
  - We need multiple outputs (1 output per class)
  - We need to estimate conditional probability:  $p(y = c | \mathbf{x})$
  - Discriminative Learning
- ▶ Softmax activation function at the output

$$\mathbf{o}(\mathbf{a}) = \text{softmax}(\mathbf{a}) = \left[ \frac{\exp(a_1)}{\sum_c \exp(a_c)} \cdots \frac{\exp(a_C)}{\sum_c \exp(a_c)} \right]^\top$$

- strictly positive
- sums to one
- ▶ Predict class with the highest estimated class conditional probability.

# Multilayer Neural Net

- Consider a network with L hidden layers.

- layer pre-activation for  $k > 0$


$$\mathbf{a}^{(k)}(\mathbf{x}) = \mathbf{b}^{(k)} + \mathbf{W}^{(k)} \mathbf{h}^{(k-1)}(\mathbf{x})$$

- hidden layer activation from 1 to L:

$$\mathbf{h}^{(k)}(\mathbf{x}) = \mathbf{g}(\mathbf{a}^{(k)}(\mathbf{x}))$$


- output layer activation ( $k=L+1$ ):

$$\mathbf{h}^{(L+1)}(\mathbf{x}) = \mathbf{o}(\mathbf{a}^{(L+1)}(\mathbf{x})) = \mathbf{f}(\mathbf{x})$$



# Capacity of Neural Nets


- Consider a single layer neural network



(from Pascal Vincent's slides)

# Capacity of Neural Nets


- Consider a single layer neural network



(from Pascal Vincent's slides)

# Capacity of Neural Nets

- Consider a single layer neural network




(from Pascal Vincent's slides)

# Universal Approximation

- Universal Approximation Theorem (Hornik, 1991):
  - “a single hidden layer neural network with a linear output unit can approximate any continuous function arbitrarily well, given enough hidden units”
- This applies for sigmoid, tanh and many other activation functions.
- However, this does not mean that there is learning algorithm that can find the necessary parameter values.

# Feedforward Neural Networks

- ▶ How neural networks predict  $f(x)$  given an input  $x$ :
  - Forward propagation
  - Types of units
  - Capacity of neural networks
- ▶ How to train neural nets:
  - Loss function
  - Backpropagation with gradient descent
- ▶ More recent techniques:
  - Dropout
  - Batch normalization
  - Unsupervised Pre-training



# Training

- Empirical Risk Minimization:

$$\arg \min_{\theta} \frac{1}{T} \sum_t l(f(\mathbf{x}^{(t)}; \theta), y^{(t)}) + \lambda \Omega(\theta)$$

- Learning is cast as optimization.

- For classification problems, we would like to minimize classification error.
  - Loss function can sometimes be viewed as **a surrogate for what we want to optimize** (e.g. upper bound)

# Stochastic Gradient Descend

- Perform updates after seeing each example:

- Initialize:  $\theta \equiv \{\mathbf{W}^{(1)}, \mathbf{b}^{(1)}, \dots, \mathbf{W}^{(L+1)}, \mathbf{b}^{(L+1)}\}$
- For  $t=1:T$

- for each training example  $(\mathbf{x}^{(t)}, y^{(t)})$

$$\Delta = -\nabla_{\theta} l(f(\mathbf{x}^{(t)}; \theta), y^{(t)}) - \lambda \nabla_{\theta} \Omega(\theta)$$

$$\theta \leftarrow \theta + \alpha \Delta$$

Training epoch  
=

Iteration of all examples

- To train a neural net, we need:

➤ **Loss function:**  $l(f(\mathbf{x}^{(t)}; \theta), y^{(t)})$

➤ A procedure to **compute gradients**:  $\nabla_{\theta} l(f(\mathbf{x}^{(t)}; \theta), y^{(t)})$

➤ **Regularizer** and its gradient:  $\Omega(\theta), \nabla_{\theta} \Omega(\theta)$

# Loss Function

- Let us start by considering a classification problem with a softmax output layer.
- We need to estimate:  $f(\mathbf{x})_c = p(y = c|\mathbf{x})$ 
  - We can maximize the log-probability of the correct class given an input:  $\log p(y^{(t)} = c|x^{(t)})$
- Alternatively, we can minimize the negative log-likelihood:
$$l(\mathbf{f}(\mathbf{x}), y) = - \sum_c 1_{(y=c)} \log f(\mathbf{x})_c = - \log f(\mathbf{x})_y$$
- As seen before, this is also known as a [cross-entropy entropy function](#) for multi-class classification problem.

# Stochastic Gradient Descend

- Perform updates after seeing each example:

- Initialize:  $\theta \equiv \{\mathbf{W}^{(1)}, \mathbf{b}^{(1)}, \dots, \mathbf{W}^{(L+1)}, \mathbf{b}^{(L+1)}\}$
  - For  $t=1:T$

- for each training example  $(\mathbf{x}^{(t)}, y^{(t)})$

$$\Delta = -\nabla_{\theta} l(f(\mathbf{x}^{(t)}; \theta), y^{(t)}) - \lambda \nabla_{\theta} \Omega(\theta)$$

$$\theta \leftarrow \theta + \alpha \Delta$$

}

Training epoch  
=

Iteration of all examples

- To train a neural net, we need:

- Loss function:  $l(f(\mathbf{x}^{(t)}; \theta), y^{(t)})$

- A procedure to compute gradients:  $\nabla_{\theta} l(f(\mathbf{x}^{(t)}; \theta), y^{(t)})$

- Regularizer and its gradient:  $\Omega(\theta), \nabla_{\theta} \Omega(\theta)$

# Multilayer Neural Net: Reminder

- Consider a network with L hidden layers.

- layer pre-activation for  $k > 0$

$$\mathbf{a}^{(k)}(\mathbf{x}) = \mathbf{b}^{(k)} + \mathbf{W}^{(k)} \mathbf{h}^{(k-1)}(\mathbf{x})$$


- hidden layer activation from 1 to L:

$$\mathbf{h}^{(k)}(\mathbf{x}) = \mathbf{g}(\mathbf{a}^{(k)}(\mathbf{x}))$$

- output layer activation ( $k=L+1$ ):

$$\mathbf{h}^{(L+1)}(\mathbf{x}) = \mathbf{o}(\mathbf{a}^{(L+1)}(\mathbf{x})) = \mathbf{f}(\mathbf{x})$$

Softmax activation function



# Gradient Computation

- Loss gradient at output


- Partial derivative:

$$\frac{\partial}{\partial f(\mathbf{x})_c} - \log f(\mathbf{x})_y = \frac{-1_{(y=c)}}{f(\mathbf{x})_y}$$

- Gradient:

$$\begin{aligned}
 & \nabla_{f(\mathbf{x})} - \log f(\mathbf{x})_y \\
 &= \frac{-1}{f(\mathbf{x})_y} \begin{bmatrix} 1_{(y=0)} \\ \vdots \\ 1_{(y=C-1)} \end{bmatrix} \\
 &= \frac{-\mathbf{e}(y)}{f(\mathbf{x})_y}
 \end{aligned}$$

↑ Indicator function



Remember:  $f(\mathbf{x})_c = p(y = c | \mathbf{x})$

# Gradient Computation

- Loss gradient at output pre-activation

- Partial derivative:


$$\frac{\partial}{\partial a^{(L+1)}(\mathbf{x})_c} - \log f(\mathbf{x})_y$$

$$= - (1_{(y=c)} - f(\mathbf{x})_c)$$

- Gradient:

$$\nabla_{\mathbf{a}^{(L+1)}(\mathbf{x})} - \log f(\mathbf{x})_y$$
$$= - (\mathbf{e}(y) - \mathbf{f}(\mathbf{x}))$$

Indicator function



# Derivation


$$\begin{aligned}
& \frac{\partial}{\partial a^{(L+1)}(\mathbf{x})_c} - \log f(\mathbf{x})_y \\
= & \frac{-1}{f(\mathbf{x})_y} \frac{\partial}{\partial a^{(L+1)}(\mathbf{x})_c} f(\mathbf{x})_y \\
= & \frac{-1}{f(\mathbf{x})_y} \frac{\partial}{\partial a^{(L+1)}(\mathbf{x})_c} \text{softmax}(\mathbf{a}^{(L+1)}(\mathbf{x}))_y \\
= & \frac{-1}{f(\mathbf{x})_y} \frac{\partial}{\partial a^{(L+1)}(\mathbf{x})_c} \frac{\exp(a^{(L+1)}(\mathbf{x})_y)}{\sum_{c'} \exp(a^{(L+1)}(\mathbf{x})_{c'})} \\
= & \frac{-1}{f(\mathbf{x})_y} \left( \frac{\frac{\partial}{\partial a^{(L+1)}(\mathbf{x})_c} \exp(a^{(L+1)}(\mathbf{x})_y)}{\sum_{c'} \exp(a^{(L+1)}(\mathbf{x})_{c'})} - \frac{\exp(a^{(L+1)}(\mathbf{x})_y) \left( \frac{\partial}{\partial a^{(L+1)}(\mathbf{x})_c} \sum_{c'} \exp(a^{(L+1)}(\mathbf{x})_{c'}) \right)}{\left( \sum_{c'} \exp(a^{(L+1)}(\mathbf{x})_{c'}) \right)^2} \right) \\
= & \frac{-1}{f(\mathbf{x})_y} \left( \frac{1_{(y=c)} \exp(a^{(L+1)}(\mathbf{x})_y)}{\sum_{c'} \exp(a^{(L+1)}(\mathbf{x})_{c'})} - \frac{\exp(a^{(L+1)}(\mathbf{x})_y)}{\sum_{c'} \exp(a^{(L+1)}(\mathbf{x})_{c'})} \frac{\exp(a^{(L+1)}(\mathbf{x})_c)}{\sum_{c'} \exp(a^{(L+1)}(\mathbf{x})_{c'})} \right) \\
= & \frac{-1}{f(\mathbf{x})_y} \left( 1_{(y=c)} \text{softmax}(\mathbf{a}^{(L+1)}(\mathbf{x}))_y - \text{softmax}(\mathbf{a}^{(L+1)}(\mathbf{x}))_y \text{softmax}(\mathbf{a}^{(L+1)}(\mathbf{x}))_c \right) \\
= & \frac{-1}{f(\mathbf{x})_y} (1_{(y=c)} f(\mathbf{x})_y - f(\mathbf{x})_y f(\mathbf{x})_c) \\
= & - (1_{(y=c)} - f(\mathbf{x})_c)
\end{aligned}$$

$$\frac{\partial \frac{g(x)}{h(x)}}{\partial x} = \frac{\partial g(x)}{\partial x} \frac{1}{h(x)} - \frac{g(x)}{h(x)^2} \frac{\partial h(x)}{\partial x}$$

# Gradient Computation

- Loss gradient for **hidden layers**

- This is getting complicated!




# Gradient Computation

- **Chain Rule:** Assume that a function  $p(a)$  can be written as a function of intermediate results  $q_i(a)$ , then:

$$\frac{\partial p(a)}{\partial a} = \sum_i \frac{\partial p(a)}{\partial q_i(a)} \frac{\partial q_i(a)}{\partial a}$$

- We can invoke it by setting:
  - $a$  be a hidden unit
  - $q_i(a)$  be a pre-activation in the layer above
  - $p(a)$  be the loss function




# Gradient Computation

- Loss gradient at hidden layers
  - Partial derivative:

$$\begin{aligned} & \frac{\partial}{\partial h^{(k)}(\mathbf{x})_j} - \log f(\mathbf{x})_y \\ = & \sum_i \frac{\partial - \log f(\mathbf{x})_y}{\partial a^{(k+1)}(\mathbf{x})_i} \frac{\partial a^{(k+1)}(\mathbf{x})_i}{\partial h^{(k)}(\mathbf{x})_j} \\ = & \sum_i \frac{\partial - \log f(\mathbf{x})_y}{\partial a^{(k+1)}(\mathbf{x})_i} W_{i,j}^{(k+1)} \end{aligned}$$

Remember:

$$a^{(k)}(\mathbf{x})_i = b_i^{(k)} + \sum_j W_{i,j}^{(k)} h^{(k-1)}(\mathbf{x})_j$$



# Gradient Computation


- Loss gradient at hidden layers
  - Gradient

$$\nabla_{\mathbf{h}^{(k)}(\mathbf{x})} - \log f(\mathbf{x})_y \\ = \mathbf{W}^{(k+1)^\top} (\nabla_{\mathbf{a}^{(k+1)}(\mathbf{x})} - \log f(\mathbf{x})_y)$$

We already know  
how to compute  
that

Remember:

$$a^{(k)}(\mathbf{x})_i = b_i^{(k)} + \sum_j W_{i,j}^{(k)} h^{(k-1)}(\mathbf{x})_j$$




# Gradient Computation

- Loss gradient at hidden layers  
(pre-activation)
  - Partial derivative:

$$\begin{aligned} & \frac{\partial}{\partial a^{(k)}(\mathbf{x})_j} - \log f(\mathbf{x})_y \\ = & \frac{\partial - \log f(\mathbf{x})_y}{\partial h^{(k)}(\mathbf{x})_j} \frac{\partial h^{(k)}(\mathbf{x})_j}{\partial a^{(k)}(\mathbf{x})_j} \\ = & \frac{\partial - \log f(\mathbf{x})_y}{\partial h^{(k)}(\mathbf{x})_j} g'(a^{(k)}(\mathbf{x})_j) \end{aligned}$$

Remember:

$$h^{(k)}(\mathbf{x})_j = g(a^{(k)}(\mathbf{x})_j)$$



# Gradient Computation

- Loss gradient at hidden layers  
(pre-activation)
  - Gradient:

$$\begin{aligned} & \nabla_{\mathbf{a}^{(k)}(\mathbf{x})} - \log f(\mathbf{x})_y \\ = & (\nabla_{\mathbf{h}^{(k)}(\mathbf{x})} - \log f(\mathbf{x})_y)^\top \nabla_{\mathbf{a}^{(k)}(\mathbf{x})} \mathbf{h}^{(k)}(\mathbf{x}) \\ = & (\nabla_{\mathbf{h}^{(k)}(\mathbf{x})} - \log f(\mathbf{x})_y) \odot [\dots, g'(a^{(k)}(\mathbf{x})_j), \dots] \end{aligned}$$

Let's look at the gradients of activation functions.

Gradient of the activation function

Remember:

$$h^{(k)}(\mathbf{x})_j = g(a^{(k)}(\mathbf{x})_j)$$


# Linear Activation Function Gradient

- Linear activation function:

$$g(a) = a$$

- Partial derivative

$$g'(a) = 1$$




# Sigmoid Activation Function Gradient

- Sigmoid activation function:

- Partial derivative

$$g'(a) = g(a)(1 - g(a))$$

$$g(a) = \text{sigm}(a) = \frac{1}{1+\exp(-a)}$$



# Tanh Activation Function Gradient


- Hyperbolic tangent (“tanh”) activation function:

$$g(a) = \tanh(a) =$$

– Partial derivative

$$= \frac{\exp(a) - \exp(-a)}{\exp(a) + \exp(-a)} = \frac{\exp(2a) - 1}{\exp(2a) + 1}$$

$$g'(a) = 1 - g(a)^2$$




# Tanh Activation Function Gradient

- Rectified linear (ReLU) activation function:

- Partial derivative

$$g'(a) = \mathbf{1}_{a>0}$$

$$g(a) = \text{reclin}(a) = \max(0, a)$$



# Stochastic Gradient Descend

- Perform updates after seeing each example:

- Initialize:  $\theta \equiv \{\mathbf{W}^{(1)}, \mathbf{b}^{(1)}, \dots, \mathbf{W}^{(L+1)}, \mathbf{b}^{(L+1)}\}$
  - For  $t=1:T$

- for each training example  $(\mathbf{x}^{(t)}, y^{(t)})$

$$\Delta = -\nabla_{\theta} l(f(\mathbf{x}^{(t)}; \theta), y^{(t)}) - \lambda \nabla_{\theta} \Omega(\theta)$$

$$\theta \leftarrow \theta + \alpha \Delta$$

}

Training epoch  
=

Iteration of all examples

- To train a neural net, we need:

- Loss function:  $l(f(\mathbf{x}^{(t)}; \theta), y^{(t)})$

- A procedure to compute gradients:  $\nabla_{\theta} l(f(\mathbf{x}^{(t)}; \theta), y^{(t)})$

- Regularizer and its gradient:  $\Omega(\theta), \nabla_{\theta} \Omega(\theta)$

# Gradient Computation


- Loss gradient of parameters

- Partial derivative (weights):

$$\begin{aligned} & \frac{\partial}{\partial W_{i,j}^{(k)}} - \log f(\mathbf{x})_y \\ = & \frac{\partial - \log f(\mathbf{x})_y}{\partial a^{(k)}(\mathbf{x})_i} \frac{\partial a^{(k)}(\mathbf{x})_i}{\partial W_{i,j}^{(k)}} \\ = & \frac{\partial - \log f(\mathbf{x})_y}{\partial a^{(k)}(\mathbf{x})_i} h_j^{(k-1)}(\mathbf{x}) \end{aligned}$$

Remember:

$$a^{(k)}(\mathbf{x})_i = b_i^{(k)} + \sum_j W_{i,j}^{(k)} h^{(k-1)}(\mathbf{x})_j$$




# Gradient Computation

- Loss gradient of parameters

- Gradient (weights):

$$\nabla_{\mathbf{W}^{(k)}} - \log f(\mathbf{x})_y \\ = (\nabla_{\mathbf{a}^{(k)}(\mathbf{x})} - \log f(\mathbf{x})_y) \quad \mathbf{h}^{(k-1)}(\mathbf{x})^\top$$



Remember:

$$a^{(k)}(\mathbf{x})_i = b_i^{(k)} + \sum_j W_{i,j}^{(k)} h^{(k-1)}(\mathbf{x})_j$$

# Gradient Computation


- Loss gradient of parameters

- Partial derivative (biases):

$$\begin{aligned} & \frac{\partial}{\partial b_i^{(k)}} - \log f(\mathbf{x})_y \\ = & \frac{\partial - \log f(\mathbf{x})_y}{\partial a^{(k)}(\mathbf{x})_i} \frac{\partial a^{(k)}(\mathbf{x})_i}{\partial b_i^{(k)}} \\ = & \frac{\partial - \log f(\mathbf{x})_y}{\partial a^{(k)}(\mathbf{x})_i} \end{aligned}$$

Remember:


$$a^{(k)}(\mathbf{x})_i = b_i^{(k)} + \sum_j W_{i,j}^{(k)} h^{(k-1)}(\mathbf{x})_j$$



# Gradient Computation

- Loss gradient of parameters
  - Gradient (biases):

$$\begin{aligned} & \nabla_{\mathbf{b}^{(k)}} - \log f(\mathbf{x})_y \\ = & \nabla_{\mathbf{a}^{(k)}(\mathbf{x})} - \log f(\mathbf{x})_y \end{aligned}$$



Remember:

$$a^{(k)}(\mathbf{x})_i = b_i^{(k)} + \sum_j W_{i,j}^{(k)} h^{(k-1)}(\mathbf{x})_j$$

# Backpropagation Algorithm

- Perform forward propagation
- Compute output gradient (before activation):

$$\nabla_{\mathbf{a}^{(L+1)}(\mathbf{x})} - \log f(\mathbf{x})_y \iff -(\mathbf{e}(y) - \mathbf{f}(\mathbf{x}))$$

- For  $k=L+1$  to 1

- Compute gradients w.r.t. the hidden layer parameters:

$$\nabla_{\mathbf{W}^{(k)}} - \log f(\mathbf{x})_y \iff (\nabla_{\mathbf{a}^{(k)}(\mathbf{x})} - \log f(\mathbf{x})_y) \mathbf{h}^{(k-1)}(\mathbf{x})^\top$$

$$\nabla_{\mathbf{b}^{(k)}} - \log f(\mathbf{x})_y \iff \nabla_{\mathbf{a}^{(k)}(\mathbf{x})} - \log f(\mathbf{x})_y$$

- Compute gradients w.r.t. the hidden layer below:


$$\nabla_{\mathbf{h}^{(k-1)}(\mathbf{x})} - \log f(\mathbf{x})_y \iff \mathbf{W}^{(k)^\top} (\nabla_{\mathbf{a}^{(k)}(\mathbf{x})} - \log f(\mathbf{x})_y)$$

- Compute gradients w.r.t. the hidden layer below (before activation):

$$\nabla_{\mathbf{a}^{(k-1)}(\mathbf{x})} - \log f(\mathbf{x})_y \iff (\nabla_{\mathbf{h}^{(k-1)}(\mathbf{x})} - \log f(\mathbf{x})_y) \odot [\dots, g'(a^{(k-1)}(\mathbf{x})_j), \dots]$$


# Computational Flow Graph

- Forward propagation can be represented as an acyclic flow graph
- Forward propagation can be implemented in a modular way:
  - Each box can be an object with an **fprop method**, that computes the value of the box given its children
  - Calling the fprop method of each box in the right order yields forward propagation



# Computational Flow Graph

- Each object also has a **bprop** method
  - it computes the gradient of the loss with respect to each child box.
  - fprop depends on the fprop output of box's children, while bprop depends on the bprop of box's parents
- By calling bprop in the **reverse order**, we obtain backpropagation



# Stochastic Gradient Descend

- Perform updates after seeing each example:

- Initialize:  $\theta \equiv \{\mathbf{W}^{(1)}, \mathbf{b}^{(1)}, \dots, \mathbf{W}^{(L+1)}, \mathbf{b}^{(L+1)}\}$
  - For  $t=1:T$

- for each training example  $(\mathbf{x}^{(t)}, y^{(t)})$

$$\Delta = -\nabla_{\theta} l(f(\mathbf{x}^{(t)}; \theta), y^{(t)}) - \lambda \nabla_{\theta} \Omega(\theta)$$

$$\theta \leftarrow \theta + \alpha \Delta$$

}

Training epoch  
=

Iteration of all examples

- To train a neural net, we need:

- Loss function:  $l(f(\mathbf{x}^{(t)}; \theta), y^{(t)})$
- A procedure to compute gradients:  $\nabla_{\theta} l(f(\mathbf{x}^{(t)}; \theta), y^{(t)})$
- Regularizer and its gradient:  $\Omega(\theta), \nabla_{\theta} \Omega(\theta)$

# Weight Decay

- L2 regularization:

$$\Omega(\boldsymbol{\theta}) = \sum_k \sum_i \sum_j \left( W_{i,j}^{(k)} \right)^2 = \sum_k \|\mathbf{W}^{(k)}\|_F^2$$

- Gradient:


$$\nabla_{\mathbf{W}^{(k)}} \Omega(\boldsymbol{\theta}) = 2\mathbf{W}^{(k)}$$

- Only applies to weights, not biases (weight decay)
- Can be interpreted as having a Gaussian prior over the weights, while performing MAP estimation.
- We will later look at Bayesian methods.

# Other Regularizers

- Using a more general regularizer, we get:

$$\frac{1}{2} \sum_{n=1}^N \{t_n - \mathbf{w}^T \phi(\mathbf{x}_n)\}^2 + \frac{\lambda}{2} \sum_{j=1}^M |w_j|^q$$



# L1 Regularization

- L1 regularization:

$$\Omega(\boldsymbol{\theta}) = \sum_k \sum_i \sum_j |W_{i,j}^{(k)}|$$

- Gradient:

$$\nabla_{\mathbf{W}^{(k)}} \Omega(\boldsymbol{\theta}) = \text{sign}(\mathbf{W}^{(k)})$$

$$\text{sign}(\mathbf{W}^{(k)})_{i,j} = 1_{\mathbf{W}_{i,j}^{(k)} > 0} - 1_{\mathbf{W}_{i,j}^{(k)} < 0}$$

- Only applies to weights, not biases (weight decay)
- Can be interpreted as having a Laplace prior over the weights, while performing MAP estimation.
- Unlike L2, L1 will push some weights to be exactly 0.

# Bias-Variance Trade-off

$$\text{expected loss} = (\text{bias})^2 + \text{variance} + \text{noise}$$

Average predictions over all datasets differ from the optimal regression function.

Solutions for individual datasets vary around their averages -- how sensitive is the function to the particular choice of the dataset.

Intrinsic variability of the target values.

$$(\text{bias})^2 = \int \{\mathbb{E}_{\mathcal{D}}[y(\mathbf{x}; \mathcal{D})] - h(\mathbf{x})\}^2 p(\mathbf{x}) d\mathbf{x}$$

$$\text{variance} = \int \mathbb{E}_{\mathcal{D}} [\{y(\mathbf{x}; \mathcal{D}) - \mathbb{E}_{\mathcal{D}}[y(\mathbf{x}; \mathcal{D})]\}^2] p(\mathbf{x}) d\mathbf{x}$$


$$\text{noise} = \iint \{h(\mathbf{x}) - t\}^2 p(\mathbf{x}, t) d\mathbf{x} dt$$

- Trade-off between bias and variance: With very flexible models (high complexity) we have low bias and high variance; With relatively rigid models (low complexity) we have high bias and low variance.
- The model with the optimal predictive capabilities has to balance between bias and variance.



# Bias-Variance Trade-off

- Consider the sinusoidal dataset. We generate 100 datasets, each containing  $N=25$  points, drawn independently from  $h(x) = \sin 2\pi x$ .




High variance



Low variance



Low bias



High bias

# Bias-Variance Trade-off

- Generalization error can be seen as the sum of the (squared) bias and the variance

